

TekBIO Kinematic Viscosity Water Bath:

It is used to determine kinematic viscosity of bitumen and cut-backs by vacuum capillary viscometers at any specified temperature.

Product Details:

Minimum Order Quantity	1 Unit
Temperature Range (deg. Celsius)	5 deg C above ambient to 150 deg C
Voltage (V)	230 V AC
Controller	PT-100 sensor
Frequency (Hz)	50 Hz
Phase	Single Phase
Control Accuracy	+/-1 deg c



Construction:

Double walled. Inside made of Stainless Steel. Outer Chamber made of CRC / G.I. duly Powder Coated. The gap between the walls filled with glass wool. With removable toughened Glass Window Panel.

Size: 4 Viscometer , 6 Viscometer , 8 Viscometer

TekBIO Rectangular Water Bath

We are engaged in providing our clients with Rectangular Water Bath. These hi-tech gadgets are extensively demanded for boiling and general purpose applications. We fabricate these products using long lasting single walled kettle element to ensure their durability.

Product Details:

Minimum Order Quantity	1 Unit
Power (W)	1000-1500 W
Shape	Rectangular
Size	35 x 25 x 10 cm, 40 x 30 x 10 cm
No of Holes	6-12 Hole
Hole Diameter	3 inch



Specifications:

Size	Rating Watts	Holes
35 x 25 x 10 cm	1000	6 Hole of 3"Dia
40 x 30 x 10 cm	1500	12 Hole of 3"Dia

TekBIO Constant Temperature Water Bath:

We are manufacture of rectangular, constant temperature water baths also. Its Inner chamber is made of stainless steel and outer body made of mild steel duly powder coated.

Product Details:

Minimum Order Quantity	1 Unit
Voltage (V)	230 V AC
Temperature Range (deg. Celsius)	5 deg C
Power (W)	1.5-2.5 W
Indicator Accuracy	1.5 deg C



Specification:

Size in Inch. L x B x H	Rating Watts
12"x 10"x 8"	1.5
15"x 12"x 10"	2
18"x 14"x 12"	2.5